



Summary

[Request a quote](#)

[Catalog](#)

| | |
|----------------|--------------------------------|
| Coax | 1 |
| Plug | Plug - Straight |
| Locking system | Push-pull |
| Matching parts | ERA.00.250.NTL |
| Series | 00 - NIM-CAMAC |

Technical details

Electrical Configuration

| | |
|----------------------------|--------------------------|
| Coax | 1 |
| Contact Termination Coax | Solder |
| R (max) | 6.1 mOhm |
| Insert configuration value | 0.25 - 1 Coax (50 Ohm) |
| Insulator | T: PTFE |
| Rated current | 4 Amps |
| Impedance | 50 Ohm |
| VSWR | 1.09 + 0.11 * f/GHz |
| Vtest | 2100 V (AC), 3000 V (DC) |
| Contact Type | Coaxial 50 Ohm (Solder) |
| Test voltage | 2.1 kV (rms) |
| Bucket Dia. | 0.6 mm (0.024in) |
| Contact Dia. | 0.7 mm (0.028in) |

https://www.lemo.com/int_en/solutions/specialties/00-nim-camac/ffa-00-250-ntaz.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Form & Material

| | |
|------------------------|---|
| Shell style / Model id | FFA - Straight plug with cable collet |
| Plug | Straight |
| Housing material | Brass (nickel plated [SAE AMS QQ N 290]) shell, collet nut, latch sleeve and mid pieces |
| Locking system | Push-pull |
| Keying | Circular, male |
| Weight | 2.57 g |


Environment

| | |
|--------------------------------------|----------------|
| Environmental protection (IP rating) | IP50 |
| Minimal temperature | -55°C / +260°C |
| F ret (min) | 100 N |
| Salt Spray Corrosion | >144 hr |

Cable fixation

| | |
|------------------------------|-----------------------|
| Cable termination protection | For cable bend relief |
| Fixation type | Cable collet |

Drawings



Dimensions

| | A | L | M |
|-----|------|------|------|
| mm. | 6.4 | 26 | 18 |
| in. | 0.25 | 1.02 | 0.71 |

https://www.lemo.com/int_en/solutions/specialties/00-nim-camac/ffa-00-250-ntaz.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.