BFL.0K.100.KAS





Image for illustrative purpose only

Summary

Request a quote

Catalog

Size

0K

Series

K - Outdoor keyed

https://www.lemo.com/int_en/solutions/originals/k-outdoor-keyed/bfl-0k-100-kas.html


LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Technical details

Form & Material

Shell style / Model id	BFL - Cap for plug (L key)		
Housing material	Brass (black chrome) shell and collet nut, nickel plated [SAE AMS QQ N 290] brass latch sleeve and mid pieces		
Keying	2 keys (gamma=75, plug: female contacts, receptacle: male contacts)		
Colour	Black		
Weight	7.92 g		
Environment			
Technical domain	Audio Video, Energy and Industrial, Medical, Test and Measurement		
Environmental sealing (IP rating)	IP68		
Temperature range	-55°C / +135°C		
Climatical Category	50/175/21		
Humidity (max)	<=95% [at 60 deg C /140 F]		
Shock Resistance	100 g [6 ms]		
Vibration	15 g [10 Hz - 2000 Hz]		
Salt Spray Corrosion	>1000 hr		

Drawings





https://www.lemo.com/int_en/solutions/originals/k-outdoor-keyed/bfl-0k-100-kas.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Dimensions

	Α	В	L	Ν
mm.	14	6	12.5	85
in.	0.55	0.24	0.49	3.35

$\underline{https://www.lemo.com/int_en/solutions/originals/k-outdoor-keyed/bfl-0k-100-kas.html}$

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.