



Summary

[Request a quote](#)

[Catalog](#)

Number of contacts Low Voltage	10
Socket / Receptacle	Socket / Receptacle - Fixed Panel Front Mounted
Locking system	Push-pull
Size	0R

https://www.lemo.com/int_en/ega-0r-310-gln.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Technical details

Electrical Configuration

Contact Termination Low voltage	PCB - Straight
Insert configuration value	0R.310 - 10 low voltage
Insulator	L: PEEK (UL 94 / V-0/1.5)
Rated current	3.5 A
Contact Type	Print (straight)
Contact Dia.	0.9
Number of contacts Low Voltage	10



Form & Material

Shell style / Model id	EGG - Fixed receptacle, key (G) or key (A)
Socket / Receptacle	Fixed Panel Front Mounted
Housing material	Crastin® PBT (Polybutylene terephthalate), gray
Locking system	Push-pull
Keying	3 keys (alpha=42, gamma=30, plug: male contacts, receptacle: female contacts)
Weight	4.75 g

Environment

Environmental sealing (IP rating)	IP50
-----------------------------------	------

Drawings



https://www.lemo.com/int_en/ega-0r-310-gln.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Dimensions

	A	B	L	M
mm.	24.5	9	14	12
in.	0.96	0.35	0.55	0.47

https://www.lemo.com/int_en/ega-0r-310-gln.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.