



Image for illustrative purpose only

## Summary

[Request a quote](#)

[Catalog](#)

|                                    |   |
|------------------------------------|---|
| Number of contacts Low Voltage     | 5   |
| Wire Size/AWG                      | 36 - 28   |
| Gender                             | Standard  |
| Socket / Receptacle                | Socket / Receptacle - Fixed Panel Front Mounted |
| Locking system                     | Push-pull                                       |
| Jacket cable outside diameter [mm] | 1.00 - 6.40 mm                                  |
| Size                               | TT  |
| Suggested matching part            | <a href="#">FGA.TT.305.KLAC31</a>               |
| Series                             | T - Small Outdoor keyed                         |

[https://www.lemo.com/int\\_en/solutions/originals/t-outdoor-keyed/ega-tt-305-kll.html](https://www.lemo.com/int_en/solutions/originals/t-outdoor-keyed/ega-tt-305-kll.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

# Technical details

## Electrical Configuration

|                                 |                               |
|---------------------------------|-------------------------------|
| Contact Termination Low voltage | Solder                        |
| R (max)                         | 8.7 mOhm                      |
| Insert configuration value      | T.305 - 5 Low Voltage         |
| Insulator                       | L: PEEK (UL 94 / V-0/1.5)     |
| Rated current                   | 1.7 A                         |
| Contact Type                    | Solder                        |
| Max. Solid Conductor            | 0.09 mm <sup>2</sup> (AWG 28) |
| Max. Stranded Conductor         | 0.05 mm <sup>2</sup> (AWG 30) |
| Bucket Dia.                     | 0.4 mm (0.016in)              |
| Contact Dia.                    | 0.35 mm (0.01in)              |
| Number of contacts Low Voltage  | 5                             |
| Wire Size/AWG                   | 36 - 28                       |
| Gender                          | Standard                      |

## Form & Material

|                        |   |
|------------------------|---|
| Shell style / Model id | EG - Fixed receptacle, nut fixing   |
| Socket / Receptacle    | Fixed Panel Front Mounted   |
| Housing material       | Brass (black chrome) shell and collet nut, nickel plated [SAE AMS QQ N 290] brass latch sleeve and mid pieces |
| Locking system         | Push-pull   |
| Keying                 | A: 2 keys (alpha=30, plug: male contacts, receptacle: female contacts)  |
| Colour                 | Black   |

[https://www.lemo.com/int\\_en/solutions/originals/t-outdoor-keyed/ega-tt-305-kl.html](https://www.lemo.com/int_en/solutions/originals/t-outdoor-keyed/ega-tt-305-kl.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.


## Environment

|                                   |   |
|-----------------------------------|---|
| Technical domain                  | Energy and Industrial, Test and Measurement |
| Environmental sealing (IP rating) | IP68  |
| Endurance                         | >3000 mating cycles                         |
| Temperature range                 | -55°C / +200°C                              |
| Climatical Category               | 50/175/21                                   |
| Humidity (max)                    | <=95% [at 60 deg C /140 F]                  |
| Resistance to vibration           | 15 g [10 Hz - 2000 Hz]                      |
| Shock Resistance                  | 100 g [ 6 ms]                               |
| Salt Spray Corrosion              | >1000 hr                                    |

## Cable fixation

|                                    |                |
|------------------------------------|----------------|
| Jacket cable outside diameter [mm] | 1.00 - 6.40 mm |
|------------------------------------|----------------|

## Drawings



## Dimensions

|     | <b>A</b> | <b>B</b> | <b>e</b> | <b>E</b> | <b>L</b> | <b>M</b> | <b>N</b> | <b>S1</b> | <b>S2</b> |
|-----|----------|----------|----------|----------|----------|----------|----------|-----------|-----------|
| mm. | 10       | 10.2     | M7x0.5   | 5.5      | 16       | 1.2      | 13.5     | 6.3       | 9         |
| in. | 0.39     | 0.4      |          | 0.22     | 0.63     | 0.05     | 0.53     | 0.25      | 0.35      |

## Recommended By Lemo

### Accessories

Compatible cap

[BRE.TT.200.KAZ](#)

[https://www.lemo.com/int\\_en/solutions/originals/t-outdoor-keyed/ega-tt-305-kl.html](https://www.lemo.com/int_en/solutions/originals/t-outdoor-keyed/ega-tt-305-kl.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.