



Summary

[Request a quote](#)

[Catalog](#)

| | |
|----------------|-----------|
| Triax | 1 |
| Locking system | Push-pull |
| Size | T7 |

Technical details

Electrical Configuration

| | |
|---------------------------|---------|
| Triax | 1 |
| Contact Termination Triax | Solder |
| Rated current | 12 Amps |
| Contact Type | Solder |

Form & Material

| | |
|------------------------|---|
| Shell style / Model id | FAZ - Plug, collet clamp |
| Housing material | Brass (chrome plated [SAE AMS 2460]) shell and collet nut, nickel plated [SAE AMS QQ N 290] brass latch sleeve and mid pieces |
| Locking system | Push-pull |
| Keying | Circular, male |
| Weight | 150 g |

https://www.lemo.com/int_en/faz-t7-675-cta04c.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Environment

| | |
|-----------------------------------|----------------------------|
| Environmental sealing (IP rating) | IP68 |
| Endurance | 5000 mating cycles |
| Temperature range | -55°C / +250°C |
| Humidity (max) | <=95% [at 60 deg C /140 F] |
| Shock Resistance | 100 g [6 ms] |
| Vibration | 15 g [10 Hz - 20000 Hz] |
| Salt Spray Corrosion | >1000 hr |

Cable fixation

| | |
|------------------------------|--|
| Cable termination protection | Standard back nut (no additional protection) |
| Fixation type | Cable collet |

Drawings



Dimensions

| | A | L | S1 | S2 |
|-----|----------|----------|-----------|-----------|
| mm. | 23.5 | 86 | 22 | 20 |
| in. | 0.93 | 3.39 | 0.87 | 0.79 |

https://www.lemo.com/int_en/faz-t7-675-cta04c.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.