



Image for illustrative purpose only

Summary

Request a quote

Catalog		
Locking system	Push-pull	
Size	2S	
Series	S - Indoor Stepped Insert	

Technical details

Electrical Configuration

Number of contacts Low Voltage	1	
Insert configuration value	2S.130 - 1 Low Voltage	
Rated current	30 A	
Test voltage (kV DC)	3	
Form & Material		
Housing material	Aluminum alloy (anodized) shell and collet nut, nicke plated [SAE AMS QQ N 290] brass latch sleeve and mid pieces	
Locking system	Push-pull	
Keying	3 keys (alpha=42, gamma=30, plug: male contacts, receptacle: female contacts)	
Weight	4.97 g	
Environment		
Technical domain	Audio Video, Energy and Industrial, Semiconductor, Test and Measurement	
Environmental sealing (IP rating)	IP50	
Endurance	5000 mating cycles	
Temperature range	-55°C / +250°C (max. temperature valid for short periods of use.)	
Climatical Category	50/175/21	
Humidity (max)	<=95% [at 60 deg C /140 F]	
Shielding (min)	75 dB (10 MHz)	
Shielding (min)	40 dB (1 GHz)	
Shock Resistance	100 g [6 ms]	
Vibration	15 g [10 Hz - 2000 Hz]	
Salt Spray Corrosion	>144 hr	
Cable fixation		
Cable termination protection	Standard back nut (no additional protection)	

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Drawings

