FGN.0M.565.ZZC





Image for illustrative purpose only

Summary

Request a quote

Catalog	
Number of contacts Low Voltage	1
	1
Wire Size/AWG	20 - 16
Locking system	Ratchet
Size	0M
Series	M - Rugged Ratchet coupling

Technical details

Electrical Configuration

_	
Number of contacts Low Voltage	1
Contact Termination Low voltage	Crimp
Contact Dia.	1.3
Wire Size/AWG	20 - 16
Form & Material	
Shell style / Model id	FG - Male crimp contact for M series, standard barrel
Housing material	Gold plated [ISO 27874] brass
Locking system	Ratchet
Keying	No keying
Weight	0.24 g
Environment	
Technical domain	Motorsport, Security and Defence, Transportation, Aerospace and UAV
Environmental sealing (IP rating)	No IP rating
EMI Shielding EIA 364-66A	>= 80 dB (1 GHz), >=70 dB (3 GHz), >= 58 dB (6 GHz), >= 40 dB (10 GHz)
Gunfire vibration	25 Hz - 2000 Hz, 3 axis (Apache helicopter)
Humidity (max)	21 days at 95%
Lighting strike EIA 364-76	10K amps - 6 times
Shock Resistance	300 g [3 ms]
Thermal shock	5 cycles: -65°C to +150°C
Vibration-Random	37.8 g rms - 3 axes, 4 hr amb [50 Hz - 2000 Hz]

Recommended By Lemo

Tools

Crimp tool

DPC.91.701.V