



# **Summary**

#### Request a quote

Catalog

Size	ОМ
Series	M - Rugged Ratchet coupling

## **Technical details**

#### Form & Material

Shell style / Model id	BGK - Blanking caps, large washer for fixed sockets(artic grip)			
Housing material	Aluminium (nickel plated [SAE AMS QQ N 290], anthracite color) shell and nut, other pieces bronze/brass			
Keying	3 keys (alpha=42, gamma=30, plug: male contacts, receptacle: female contacts)			
Weight	4.91 g			
Environment				
Technical domain	Motorsport, Security and Defence, Transportation, Aerospace and UAV			
Environmental protection (IP rating)	IP68			
Minimal temperature	-20°C / +135°C			
EMI Shielding EIA 364-66A	>= 80 dB (1 GHz), >=70 dB (3 GHz), >= 58 dB (6 GHz), >= 40 dB (10 GHz)			
Gunfire vibration	25 Hz - 2000 Hz, 3 axis (Apache helicopter)			
Humidity (max)	21 days at 95%			
Lighting strike EIA 364-76	10K amps - 6 times			
Shock Resistance	300 g [ 3 ms]			
Thermal shock	5 cycles: -65°C to +150°C			
Vibration-Random	37.8 g rms - 3 axes, 4 hr amb [50 Hz - 2000 Hz]			
Vibration-Sine	30 g, 3 axes, 12 hr [10 Hz - 2000 Hz]			
Salt Spray Corrosion	max. 48 hr			

#### $\underline{https://www.lemo.com/int\_en/solutions/optima/m-ratchet-coupling/bgk-0m-200-xaz.html}$

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMC components.

### **Dimensions**

	A	С	L	N	Р	X	
mm.	14.4	13.1	12.7	17	23.4	85	
in.	0.57	0.52	0.5	0.67	0.92	3.35	