



Image for illustrative purpose only

Summary

[Request a quote](#)

[Catalog](#)

| | |
|-------------------------|---|
| Nb of contacts Coax | 1 |
| Socket / Receptacle | Socket / Receptacle - Fixed Panel Front Mounted |
| Locking system | Push-pull |
| Size | 00 |
| Suggested matching part | FFA.00.250.DTAC29 |
| Series | 00 - NIM-CAMAC |

https://www.lemo.com/int_en/solutions/specialties/00-nim-camac/era-00-250-dtl.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Technical details

Electrical Configuration

| | |
|---|------------------------------|
| Nb of contacts Coax | 1 |
| Contact Termination Coax - Conductor fixing | Solder |
| R (max) | 6.1 mOhm |
| Insert configuration value | 0.25 - 1 Coax (50 Ohm) |
| Insulator | T: PTFE |
| Rated current | 4 A |
| Impedance | 50 Ohm |
| OHM | 50 |
| VSWR | $1.09 + 0.11 * f/\text{GHz}$ |
| Vtest | 2100 V (AC), 3000 V (DC) |
| Test voltage | 2.1 kV (rms) |
| Bucket Dia. | 0.6 mm (0.024in) |
| Contact Dia. | 0.7 mm (0.028in) |

Form & Material

| | |
|------------------------|--|
| Shell style / Model id | ERA - Fixed receptacle, nut fixing |
| Socket / Receptacle | Fixed Panel Front Mounted |
| Housing material | Brass (gold plated [ISO 27874]) shell, collet nut, brass latch sleeve and mid pieces |
| Locking system | Push-pull |
| Keying | Circular, female |
| Weight | 3.54 g |

Environment

| | |
|-----------------------------------|--------------------|
| Environmental sealing (IP rating) | IP50 |
| Endurance | 5000 mating cycles |
| F ret (min) | 100 N |

https://www.lemo.com/int_en/solutions/specialties/00-nim-camac/era-00-250-dtl.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Drawings



Dimensions

| | A | B | e | E | L | M | S1 | S3 |
|-----|----------|----------|----------|----------|----------|----------|-----------|-----------|
| mm. | 8 | 10.3 | M7x0.5 | 5.5 | 15 | 1 | 6.3 | 9 |
| in. | 0.31 | 0.41 | | 0.22 | 0.59 | 0.04 | 0.25 | 0.35 |

Recommended By Lemo

Accessories









Compatible cap

[BRE.00.200.NAS](#)

https://www.lemo.com/int_en/solutions/specialties/00-nim-camac/era-00-250-dtl.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Cables

| Cable PartNumber | Material | Colour | Cable image |
|---------------------|-----------|--------|--|
| 159580 | PVC | Black |  |
| 17420 | PVC | Black |  |
| 17450 | COPOLYMER | Black |  |
| 178190 | PTFE | Brown | |
| 18000 | PTFE | Brown |  |
| 18700 | PTFE | White |  |
| 18800 | PTFE | White | |
| 196270 | PTFE | White | |
| 31600 | PTFE | Brown | |
| 62000 | PVC | Black |  |
| CCX.50.030.083.180B | | white | |
| CCX.50.RG0.58AU14B | FEP | white | |
| CCX.50.RG1.74-U25N | PVC | Black | |
| CCX.50.RG1.74AU28N | PVC | Black | |
| CCX.50.RG1.74AU28N | PVC | Black |  |
| CCX.50.RG1.74U25N | PVC | Black | |
| CCX.50.RG1.78BU18M | FEP | Brown | |
| CCX.50.RG1.78BU18M | PTFE | Brown | |
| CCX.50.RG1.88AU24B | TFE | white | |
| CCX.50.RG1.88AU26B | PFA | White | |
| CCX.50.RG1.88AU26B | PTFE | White | |
| CCX.50.RG1.96AU19B | PTFE | White | |
| CCX.50.RG1.96AU20B | PFA | White | |
| CCX.50.RG3.16BU26M | FEP | Brown | |
| CCX.50.RG3.16U28M | PTFE | Brown | |
| CCX.75.040.195327G | PVC | Grey | |
| CCX.75.RG0.59BU62N | PVC | Black |  |
| CCX.75.RG1.79BU26M | FEP | Brown | |
| CCX.75.RG1.87AU26B | PFA | White | |
| CCX.75.RG1.87AU27B | PTFE | White |  |
| CCX.93.RG0.62AU62N | PVC | Black |  |
| CCX.95.RG1.80BU36M | PTFE | Brown |  |
| CCX.95.RG1.95AU37B | PFA | White | |

https://www.lemo.com/int_en/solutions/specialties/00-nim-camac/era-00-250-dtl.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.