



## Summary

[Request a quote](#)

Low Voltage	7
High Voltage	1
Plug	Plug - Straight
Locking system	Push-pull
Jacket cable outside diameter [mm]	7.10 - 7.50 mm
Size	3E
Matching parts	<a href="#">ERA.3E.707.CLL</a>
Series	E - Outdoor Stepped Insert

## Technical details

### Electrical Configuration

Contact Termination Low voltage	Solder
Contact Termination High voltage	Solder
Insert configuration value	3E.707 - 1 High V. 7 Low V.
Insulator	L: PEEK (UL 94 / V-0/1.5)
Rated current	LV 8, HV 3 Amps
Test voltage LV Ue (kV rms)	1
Working voltage HV contact - Us (kV rms)	2.1
Contact Type	Solder
Low Voltage	7
High Voltage	1

[https://www.lemo.com/int\\_en/solutions/originals/e-outdoor-stepped-insert/ffa-3e-707-clac75z.html](https://www.lemo.com/int_en/solutions/originals/e-outdoor-stepped-insert/ffa-3e-707-clac75z.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

## Form & Material

Shell style / Model id	FFA - Straight plug, cable collet and nut for fitting a bend relief
Plug	Straight
Housing material	Brass (chrome plated [SAE AMS 2460]) shell, collet nut and latch sleeve, nickel plated [SAE AMS QQ N 290] brass mid pieces
Locking system	Push-pull
Keying	Hermaphroditic keying (half moon insert) with male pin 1
Variant	Nut for fitting a bend relief
Weight	70.41 g


## Environment

Technical domain	Energy and Industrial, Test and Measurement
Environmental protection (IP rating)	IP68
Minimal temperature	-55°C / +200°C
Climatical Category	50/175/21
Humidity (max)	<=95% [at 60 deg C /140 F]
Shielding (min)	95 dB (10 MHz)
Shielding (min)	80 dB (1 GHz)
Shock Resistance	100 g [ 6 ms]
Vibration	15 g [10 Hz - 2000 Hz]
Salt Spray Corrosion	>1000 hr

## Cable fixation

Cable termination protection	For cable bend relief
Fixation type	Cable collet
Jacket cable outside diameter [mm]	7.10 - 7.50 mm

## Drawings



[https://www.lemo.com/int\\_en/solutions/originals/e-outdoor-stepped-insert/ffa-3e-707-clac75z.html](https://www.lemo.com/int_en/solutions/originals/e-outdoor-stepped-insert/ffa-3e-707-clac75z.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

## Dimensions

	<b>A</b>	<b>L</b>	<b>M</b>	<b>S2</b>
mm.	19	60	40	15
in.	0.75	2.36	1.57	0.59

[https://www.lemo.com/int\\_en/solutions/originals/e-outdoor-stepped-insert/ffa-3e-707-clac75z.html](https://www.lemo.com/int_en/solutions/originals/e-outdoor-stepped-insert/ffa-3e-707-clac75z.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.