

## Summary

[Request a quote](#)

[Catalog](#)

Number of contacts Low Voltage	7
Wire Size/AWG	32 - 24
Gender	Standard
Plug	Plug - Straight
Locking system	Push-pull
Jacket cable outside diameter [mm]	2.70 - 3.90 mm
Size	1P
Matching parts	<a href="#">PNC.M0.7SL.LJ</a>
Series	REDEL P - Push-Pull

## Technical details

[https://www.lemo.com/int\\_en/solutions/redel/redel-p-push-pull/pfc-m0-7sl-ac39jz.html](https://www.lemo.com/int_en/solutions/redel/redel-p-push-pull/pfc-m0-7sl-ac39jz.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

## Electrical Configuration

Contact Termination Low voltage	Solder
R (max)	6.5 mOhm
Insert configuration value	1P.M07 - 7 Low Voltage
Insulator	L: PEEK (UL 94 / V-0/1.5)
Rated current	5 Amps
Test voltage (kV rms) Contact-contact	1.05
Contact Type	Solder
Max. Solid Conductor	0.14 mm <sup>2</sup> (AWG 26)
Max. Stranded Conductor	0.14 mm <sup>2</sup> (AWG 26)
Air clearance	0.85 mm
Creepage distance	0.85 mm
Bucket Dia.	0.6 mm (0.024in)
Contact Dia.	0.7 mm (0.0275in)
Number of contacts Low Voltage	7
Wire Size/AWG	32 - 24
Gender	Standard

## Form & Material

Shell style / Model id	PF - Straight plug with cable collet and nut for fitting a bend relief, watertight
Plug	Straight
Housing material	PEI (Polyetherimide), gray
Locking system	Push-pull
Keying	2 keys (alpha=80, Plug: male contacts, Receptacle: female contacts)
Variant	Yellow collet nut for bend relief
Weight	4.75 g

[https://www.lemo.com/int\\_en/solutions/redel/redel-p-push-pull/pfc-m0-7sl-ac39jz.html](https://www.lemo.com/int_en/solutions/redel/redel-p-push-pull/pfc-m0-7sl-ac39jz.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.


## Environment

Technical domain	Energy and Industrial, Medical, Test and Measurement, Transportation, Aerospace and UAV
Environmental protection (IP rating)	IP64
Minimal temperature	-50°C / +170°C
F ret (max)	150 N
F ret (min)	50 N
Steam sterilization	> 100 times (with potting on rear connection)

## Cable fixation

Cable termination protection	For cable bend relief
Fixation type	Cable collet
Jacket cable outside diameter [mm]	2.70 - 3.90 mm

## Drawings



## Recommended By Lemo




### Accessories

### Tools

[https://www.lemo.com/int\\_en/solutions/redel/redel-p-push-pull/pfc-m0-7sl-ac39jz.html](https://www.lemo.com/int_en/solutions/redel/redel-p-push-pull/pfc-m0-7sl-ac39jz.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

# Cables

Cable PartNumber	Material	Colour	Cable image
CMN.07.T26.037QGZE	TPR (medical)	Grey	
7041	PVC	Grey	
7050	PVC	Black	

[https://www.lemo.com/int\\_en/solutions/redel/redel-p-push-pull/pfc-m0-7sl-ac39jz.html](https://www.lemo.com/int_en/solutions/redel/redel-p-push-pull/pfc-m0-7sl-ac39jz.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.