## SKP.M10.GLVJ





### **Summary**

#### Request a quote

Catalog				
Number of contacts Low Voltage	10			
Wire Size/AWG	30 - 22			
Socket / Receptacle	Socket / Receptacle - Fixed Panel Rear Mounted			
Locking system	Push-pull			
Size	SP			
Series	REDEL SP - Inner Push-Pull			

### **Technical details**


#### **Electrical Configuration**


SP.M10 - 10 Low V.	
L: PEEK (UL 94 / V-0/1.5)	
4.2 Amps	
0.7	
10	
30 - 22	

#### Form & Material

Shell style / Model id	SKSP - Fixed socket, key (N) or keys (P, S and T), with two nuts (back panel mounting), yellow front nut and elbow print contacts		
Socket / Receptacle	Fixed Panel Rear Mounted		
Housing material	Proprietary sulfone, gray		
Locking system	Push-pull		
Keying	3 keys (alpha=0, gamma=60, plug: male contacts, receptacle: female contacts)		
Variant	Yellow front nut		
Weight	6.6 g		
Environment			
Technical domain	Medical		
Environmental protection (IP rating)	IP50		
Minimal temperature	-50°C / +170°C		
Cable fixation			
Cable termination protection	Standard back nut (no additional protection)		

# **Drawings**







### **Dimensions**

	A	N	е	Emax	L
mm.	18.5	23.5	M14x1	8.5	36.5
in.	0.73	0.93		0.33	1.44